

IDS™
-200

Bovie®

ELECTROSURGERY

FOR THE HOSPITAL OPERATING ROOM AND SURGERY CENTER



ELECTROSURGICAL GENERATOR

CUTTING EDGE

200 watts of Cutting power

COMPETENCE

Enough power to perform most hospital OR procedures and any surgery center procedure

VERSATILITY

Offers two (2) modes of Pure Cut, ten (10) modes of Blend, two (2) modes of Coagulation, Bipolar Coagulation and BovieFCFS™ technology allowing the Doctor to move almost effortlessly from Monopolar to Bipolar during procedure

AFFORDABLE

The highest in safety and quality were built into a 200 watt generator for maximum reliability and minimum expense

SECURITY

The IDS-200 is designed with state-of-the-art safety features including Bovie NEM™ pad sensing technology which monitors the return electrode for optimum patient protection. BovieDED™ monitors all functions of the generator to ensure constant safety for the patient, doctor and OR staff





RELIABILITY

The IDS-200 is backed by Bovie's two (2) year manufacturer's limited warranty

OTHER OPTIONAL
ACCESSORIES

| | | |
|---|--|---|
| Disposable & Reusable Pencils* | Disposable Grounding Pads* | Monopolar & Bipolar Footswitches |
|  |  |  |
| ESP1 & ESPR | ESRE & ESREC | BV-1253B & BV-1254B |

| | | |
|---|--|---|
| Disposable Suction Coagulator* | Reusable SuperCut™ Tungsten Needle* | Resistick II™ Coated Blade* |
|  |  |  |
| SCH10 Handswitch | ES60R | ES01T |

| | | | |
|---|---|--|--|
| Disposable and Reusable Electrodes* | | Bipolar Forceps* | Bipolar Forcep Cord* |
| Blade | Ball | Bayonet | Reusable |
|  |  |  |  |
| ES01 | ES20 | A821 | A827V |

*More styles available

Industry-standard accessories fit most electrosurgical generators

Additional accessories available — contact your Bovie representative for details.

TECHNICAL
SPECIFICATIONS

Technical Specifications...


| | | | |
|--|----------------------|--------------------------------------|------------------------|
| Dimensions: | | Line Voltage: | Line Frequency: |
| Height | 15.30 cm (6.00 in.) | 100-240 VAC | 50 - 60 Hz |
| Width | 31.10 cm (12.25 in.) | | |
| Depth | 41.30 cm (16.25 in.) | Output Type | Duty Cycle |
| Weight | < 8.75 kg (< 19 lbs) | RF ISOLATED <input type="checkbox"/> | 10 S/30 S |
| Monopolar | Output Power | Output Frequency | Rep Rate |
| Cut | 200 W @ 300 Ω | 490 kHz ± 5 kHz | N/A |
| Blend | 200 W @ 300 Ω | 490 kHz ± 5 kHz | 30 kHz ± 5 kHz |
| Pinpoint | 120 W @ 500 Ω | 490 kHz ± 5 kHz | 30 kHz ± 5 kHz |
| Spray | 80 W @ 500 Ω | 490 kHz ± 5 kHz | 30 kHz ± 5 kHz |
| Bipolar | 80 W @ 150 Ω | 490 kHz ± 5 kHz | 30 kHz ± 5 kHz |
| Warranty: limited two (2) year on unit only | | | |

IDS™ -200 Unit



BV-IDS-CS Stand
(Optional)

Smoke Evacuation System
(Optional)



Bovie Medical Corporation • 5115 Ulmerton Road • Clearwater, FL 33760 • www.boviemed.com • sales@boviemed.com
U.S. Phone 1-800-537-2790 • Fax 1-800-323-1640 • Int'l Phone +1-727-384-2323 • Fax +1-727-347-9144

Bovie® is a registered trademark of Bovie Medical Corporation. IDS™ is a trademark of Bovie Medical Corporation.